

Bush Hog® TOUGH

Flat Deck Side Discharge Finishing Mowers

BUSH HOG® TOUGH FEATURES

TOUGH Fabricated 7 Gauge Decks

TOUGH Cat 3 Drivelines

TOUGH Commercial Grade
Greaseable Spindles

TOUGH 5 Year Gearbox Limited Warranty

TOUGH Kevlar Reinforced Belt

TOUGH Powder Coat Paint



Model FTH-720

MODELS	FTH-600	FTH-720
Cutting Width	60 inches	72 inches
Cutting Height (1/2 inch increments)	1 to 6 inches	1 to 6 inches
Tractor HP Range	15 - 35 PTO	20 - 40 PTO
Type Hitch	Category I	Category I
Size Blades	1/4 x 21/2 x 21 inches	1/4 x 21/2 x 25 inches
Number of Blades	3	3
Blade Tip Speed	18,231 FPM	18,272 FPM
Blade Overlap	1 1/2 inches	1 1/2 inches
Blade Uplift	Parallel	Parallel
Driveline Size	ASAE Category 3	ASAE Category 3
Front Roller Size (optional)	3 x 5 inches	3 x 5 inches
Discharge	Right Side	Right Side
Deck Plate	7 gauge	7 gauge
Tire Size (solid tire or pneumatic tire)	31/4 x 101/4 inches	31/4 x 101/4 inches
Belt	"B" Size Kevlar	"B" Size Kevlar
Gearbox	45 HP	45 HP
Tractor PTO Speed	540 RPM	540 RPM
Belt Adjustment	Spring Loaded Idler	Spring Loaded Idler
Approximate Weight	560 lbs	588 lbs
Options	Front Roller Roller Bearing Kit	Front Roller Roller Bearing Kit

Warranty 1 year limited warranty with a 5 year gearbox limited warranty

FEATURES

- Wide discharge • Floating top link • High blade tip speeds • Easy lift tabs for quick lubrication of spindles
- Available in major tractor colors

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



P. O. BOX 849
MOBILE, ALABAMA 36601 USA
EMAIL: mobile@opico.com
TEL +1 251 438 9881