

Bush Hog® TOUGH

2212 Flex Wing Rotary Cutter

Recommended Tractor HP 50 to 75 PTO

BUSH HOG® TOUGH FEATURES

TOUGH Heavy Duty Axle Turn Buckles

TOUGH Greaseable Axle Pivot Points With Spring Steel Bushings For Extended Wear

TOUGH Dual Spring Shock Absorption

TOUGH Driveline Retaining Ring

AVAILABLE IN MAY 2008



MODEL	2212
Cutting Width	12 ft
Cutting Capacity	1 1/2 inch diameter
Cutting Height	2 to 14 inches
Overall Width and Length (from Clevis to Wheel Hub at Transport Height)	12 ft 8 inches x 13 ft 3 inch
Transport Width (from wing skid to wing skid)	5 ft 8 inches
Tractor PTO	540 RPM
Minimum Tractor HP	50 PTO
Deck Thickness	10 gauge
Side Bands	7 gauge x 12 inches
Gearbox HP	160 -Transfer, 75 - Center, 75 - Wings
PTO Driveline	ASAE Cat. 4 (540 RPM)
Wing Driveline	ASAE Cat. 3
Slip Clutches	(3) Multiple Plate Clutches
Blade Tip Speed	15,604 FPM
Blades	1/2 x 4 inch Uplift with 6 inch Overlap
Type Hitch	Self Leveling with Swivel Clevis
Wing Flex (Operating)	87° Up to 22° Down
Tires	Choice of Laminated Tire, Used Aircraft Tire, or Pneumatic 15 inch Wheel
Axles	Greaseable pivot points with bushings
Wheel Shock Protection	Springs on Center Section
Deflectors	Banding and Belting; Chains Optional
Options	Chain Shielding, Valve & Stand Kit
Warranty	1 year limited warranty with a 5 year gearbox limited warranty

BUSH HOG EXCLUSIVE:

Driveline safety retaining rings



P. O. BOX 849
MOBILE, ALABAMA 36601 USA
EMAIL: mobile@opico.com
TEL +1 251 438 9881