

Bush Hog® TOUGH

2720 Flex Wing Rotary Cutters

Recommended Tractor HP Minimum 90 PTO

BUSH HOG® TOUGH FEATURES

- TOUGH 10 Gauge Steel Deck
- TOUGH 7 Gauge Strongbacks
- TOUGH 1/4 Inch Sidebands
- TOUGH Heavy Duty Wheel Hubs And Axle Spindles
- TOUGH Independent Spring Cushion On Each Axle Arm
- TOUGH Heavy Duty Axle With Turnbuckles
- TOUGH Greaseable Axle Pivot Points
- TOUGH Driveline Safety Retaining Rings
- TOUGH 5 Year Gearbox Limited Warranty
- TOUGH Powder Coat Paint



MODEL	2720
Cutting Width	20 ft
Cutting Capacity	2 1/2 inch Diameter
Cutting Height	2 to 14 inches
Overall Width x Length (from clevis to wheel hub at transport height)	21 ft x 15 ft 11 inches
Transport Width (outside wing skid to outside wing skid)	11 ft
Tractor PTO	540 RPM/1000 RPM
Minimum Tractor HP	90 PTO
Deck Thickness	10 gauge
Side Bands	1/4 x 10 1/2 inches
Gearbox HP	235 - Transfer, 190 - Center, 190 - Wings
PTO Drivelines	Input: Constant Velocity or Cardan/jackshaft - Cat. 5 (540 RPM), Cat. 4 or 5 (1000 RPM)
Wing Drivelines	ASAE Cat. 5
Slip Clutches	(3) 4 - Friction Plates
Blade Tip Speed	16,328 FPM/540 RPM; 16,000 FPM/1000 RPM
Blades	1/2 x 4 inch Uplift with 6 inch Overlap
Type Hitch	Self Leveling with Perma-Level® Hitch, or Available with 2 5/16 inch Ball Hitch
Wing Flex	87° Up to 22° Down
Tires	Laminated Tire, Used Aircraft Tire, Foam Filled Used Aircraft Tire, Pneumatic 15 inch Wheel (tire not included), 15 inch x 6 inch Wheel for 9.5L x 15 inch Tire, Modified Laminated Tire with 10 Bolts
Axles	Dual or Tandem Walking Axles for Center Section; Single Axle, Dual Axle or Tandem Walking Axle for Wings
Wheel Shock Protection	Independent Spring Shock Absorption on Each Axle Arm
Deflectors	Standard Front Belting, Rear Metal Band
Options	Chain Shielding, Valve Stand Kit, Grass Baffle Kit, Deck Rings, Straight Blade Bar, Shredder Kit
Warranty	1 year limited warranty with a 5 year gearbox limited warranty

FEATURES • Perma-Level® Hitch • High blade tip speeds • Deep sidebands • Heavy duty wheel hubs • Quick detach gearbox shields

BUSH HOG EXCLUSIVE:

Driveline safety retaining rings

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



P. O. BOX 849
MOBILE, ALABAMA 36601 USA
EMAIL: mobile@opico.com
TEL +1 251 438 9881