

Bush Hog® TOUGH

3715 Flex Wing Rotary Cutters

Recommended Tractor HP Minimum 80 PTO

BUSH HOG® TOUGH FEATURES

- TOUGH 7 Gauge Deck Construction
- TOUGH 7 Gauge Strongbacks
- TOUGH 1/4 Inch Sidebands
- TOUGH Independent Spring Cushion At Each Axle Arm
- TOUGH Heavy Duty Axle Turn Buckles
- TOUGH Greaseable Axle Pivot Points
- TOUGH Heavy Duty Wheel Hubs And Axle Spindles
- TOUGH Driveline Safety Retaining Rings
- TOUGH 5 Year Gearbox Limited Warranty
- TOUGH Powder Coat Paint



MODEL	3715
Cutting Width	15 ft
Cutting Capacity	3 1/2 inch Diameter
Cutting Height	2 to 14 inches
Overall Width x Length (from clevis to wheel hub at transport height)	15 ft 6 inches x 14 ft 6 inches
Transport Width (outside wing skid to outside wing skid)	8 ft 11 inches
Tractor PTO	540 RPM/1000 RPM
Minimum Tractor HP	80 PTO
Deck Thickness	7 gauge
Side Bands	1/4 x 10 ¹ / ₂ inches
Gearbox HP	235 - Transfer, 190 - Center, 190 - Wings
PTO Drivelines	Input: Constant Velocity or Cardan/jackshaft - Cat. 5 (540 RPM), Cat. 4 or 5 (1000 RPM)
Wing Drivelines	ASAE Cat. 5
Slip Clutches	(3) 4 - Friction Plates
Blade Tip Speed	16,289 FPM/540 RPM; 16,000 FPM/1000 RPM
Blades	1/2 x 4 inch Uplift with 6 inch Overlap
Type Hitch	Self Leveling with Perma-Level® Hitch or available with 2 5/16 inch ball hitch or Swivel Clevis hitch
Wing Flex	87° Up to 22° Down
Tires	Laminated Tire, Used Aircraft Tire, Foam Filled Used Aircraft Tire, Pneumatic 15 inch Wheel (tire not included), 15 inch x 6 inch Wheel for 9.5L x 15 inch Tire, Modified Laminated Tire with 10 Bolts
Axles	Dual or Tandem Walking Axles for Center Section; Single Axle, Dual Axle or Tandem Walking Axle for Wings
Wheel Shock Protection	Independent Spring Absorption on Each Axle
Deflectors	Standard Front Belting/Rear Band
Options	Tandem Walking Axles, Manual Wing Lift, Chain Shielding Front and Rear, Valve & Stand Kit, Grass Baffles, Deck Rings
Warranty	1 year limited warranty with a 5 year gearbox limited warranty

- | FEATURES | |
|----------|---|
| | <ul style="list-style-type: none"> • Perma Level Hitch • Cylinder style anti wrap device around lower gearbox housing • High blade tip speeds • Deep Sidebands • Heavy duty wheel hubs • Quick detach gearbox shields |

BUSH HOG EXCLUSIVE: Driveline safety retaining rings

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



P. O. BOX 849
 MOBILE, ALABAMA 36601 USA
 EMAIL: mobile@opico.com
 TEL +1 251 438 9881