

# Bush Hog® TOUGH

## 3710 Single Wing

### Flex Series Rotary Cutters

Recommended Tractor HP Minimum 80 PTO

#### BUSH HOG® TOUGH FEATURES

TOUGH 7 Gauge Deck Construction

TOUGH 7 Gauge Strongbacks

TOUGH 1/4 Inch Sidebands

TOUGH Independent Spring Cushion At Each Axle Arm

TOUGH Heavy Duty Axle Turn Buckles

TOUGH Greaseable Axle Pivot Points

TOUGH Heavy Duty Wheel Hubs And Axle Spindles

TOUGH Driveline Safety Retaining Rings

TOUGH 5 Year Gearbox Limited Warranty

TOUGH Powder Coat Paint

Model 3710



MODEL	3710
Cutting Width	10 ft 6 inches
Cutting Capacity	3 1/2 inch diameter
Cutting Height	2 to 14 inches
Overall Width x Length (from clevis to wheel hub at transport height)	11 ft 8 inches x 14 ft 6 inches
Transport Width (from weight box to wing skid)	8 ft
Tractor PTO	540 RPM/1000 RPM
Minimum Tractor HP	80 PTO
Deck Thickness	7 gauge
Side Bands	1/4 x 10 1/2 inches
Gearbox HP	235/Transfer, 190/Center & Wing
PTO Driveline	Input: Constant Velocity or Cardan/jackshaft - Cat. 5 (540 RPM) Cat. 4 or 5 (1000 RPM)
Wing Driveline	ASAE Cat. 5
Slip Clutches	(2) 4 Friction Plates
Blade Tip Speed	16,289 FPM/540 RPM; 16,000 FPM/1000 RPM
Blades	1/2 x 4 inches – Uplift with 6 inch Overlap
Type Hitch	Self Leveling with Perma Level Hitch® or 2 5/16 inch Ball Hitch or Swivel Clevis Hitch
Wing Flex	87° Up to 22° Down
Tires	Laminated, Pneumatic or Aircraft
Axles	Greaseable with bushings
Wheel Shock Protection	Independent Springs/Each Axle
Deflectors	Standard Front Belting and Rear Band, Optional Chains Front and Rear
Options	Chain Shielding, Tandem Walking Axle, Deck Rings

#### Warranty

1 year limited warranty with a 5 year gearbox limited warranty

- Perma Level Hitch • Cylinder style anti wrap device around lower gearbox housing
- High blade tip speeds • Deep sidebands • Heavy duty wheel hubs • Quick detach gearbox shields

#### FEATURES

**BUSH HOG EXCLUSIVE:**

Driveline safety retaining rings

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



P. O. BOX 849  
MOBILE, ALABAMA 36601 USA  
EMAIL: [mobile@opico.com](mailto:mobile@opico.com)  
TEL +1 251 438 9881