

Bush Hog® TOUGH

3710 Single Wing

Flex Series Rotary Cutters

Recommended Tractor HP Minimum 80 PTO

BUSH HOG® TOUGH FEATURES

TOUGH 7 Gauge Deck Construction

TOUGH 7 Gauge Strongbacks

TOUGH 1/4 Inch Sidebands

TOUGH Independent Spring Cushion At Each Axle Arm

TOUGH Heavy Duty Axle Turn Buckles

TOUGH Greaseable Axle Pivot Points

TOUGH Heavy Duty Wheel Hubs And Axle Spindles

TOUGH Driveline Safety Retaining Rings

TOUGH 5 Year Gearbox Limited Warranty

TOUGH Powder Coat Paint

Model 3710



| MODEL | 3710 |
|---|---|
| Cutting Width | 10 ft 6 inches |
| Cutting Capacity | 3 1/2 inch diameter |
| Cutting Height | 2 to 14 inches |
| Overall Width x Length (from clevis to wheel hub at transport height) | 11 ft 8 inches x 14 ft 6 inches |
| Transport Width (from weight box to wing skid) | 8 ft |
| Tractor PTO | 540 RPM/1000 RPM |
| Minimum Tractor HP | 80 PTO |
| Deck Thickness | 7 gauge |
| Side Bands | 1/4 x 10 1/2 inches |
| Gearbox HP | 235/Transfer, 190/Center & Wing |
| PTO Driveline | Input: Constant Velocity or Cardan/jackshaft - Cat. 5 (540 RPM) Cat. 4 or 5 (1000 RPM) |
| Wing Driveline | ASAE Cat. 5 |
| Slip Clutches | (2) 4 Friction Plates |
| Blade Tip Speed | 16,289 FPM/540 RPM; 16,000 FPM/1000 RPM |
| Blades | 1/2 x 4 inches – Uplift with 6 inch Overlap |
| Type Hitch | Self Leveling with Perma Level Hitch® or 2 5/16 inch Ball Hitch or Swivel Clevis Hitch |
| Wing Flex | 87° Up to 22° Down |
| Tires | Laminated, Pneumatic or Aircraft |
| Axles | Greaseable with bushings |
| Wheel Shock Protection | Independent Springs/Each Axle |
| Deflectors | Standard Front Belting and Rear Band, Optional Chains Front and Rear |
| Options | Chain Shielding, Tandem Walking Axle, Deck Rings |
| Warranty | 1 year limited warranty with a 5 year gearbox limited warranty • Perma Level Hitch • Cylinder style anti wrap device around lower gearbox housing • High blade tip speeds • Deep sidebands • Heavy duty wheel hubs • Quick detach gearbox shields |

FEATURES

BUSH HOG EXCLUSIVE:

Driveline safety retaining rings

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



P. O. BOX 849
MOBILE, ALABAMA 36601 USA
EMAIL: mobile@opico.com
TEL +1 251 438 9881