

Bush Hog® TOUGH

2010 Series Rotary Cutters

BUSH HOG® TOUGH FEATURES

TOUGH 5 Year Gearbox Limited Warranty

TOUGH 7 Gauge Sidebands

TOUGH Replaceable Wide Skids

TOUGH Cushioned Axle Arms

TOUGH Powder Coat Paint



MODEL	2010
Cutting Width	9 ft 9 inches
Cutting Capacity	2 inches
Dimensions (width x length)	10 ft 3 inches x 9 ft 4 inches (Lift), 10 ft 3 inches x 13 ft (Pull)
Type Hitch	3 Point Cat. II & III Standard & Quick Hitch, Center Pull Self Leveling or Semi-Mount Cat. II & III
Cutting Height	2 to 12 inches
Deck Thickness	11 gauge
Side Bands	7 gauge x 10 inches
Minimum Tractor HP	40 PTO (Pull), 60 PTO (Lift)
Driveline	ASAE Category 4
Cross Shaft	Rubber Element
Gearbox HP	120 Main and 90 Outboard
Tractor PTO Speed	540/1000 RPM
Driveline Protection	4 Plate PTO Slip Clutch
Height Adjustment	Choice of Manual Height Bundle or Hydraulic Cylinder
Blade Holder(s)	Round Pans
Blades	1/2 x 4 inches - Corner Uplift
Blade Tip Speed	15,778 FPM/540 RPM; 15,708 FPM/1000 RPM
Tires	Laminated Tire on Lift and Semi-Mount Models, Laminated Tire or 15 inch Automotive Wheel on Pull Models, Used Aircraft Tires on Pull Type Only
Axles	Adjustable Axle Arms for Row Spacing, Choice of Single or Dual Axles on Pull Models
Deflectors	Standard Front Belting and Rear Bands (Chains Optional)
Safety Tow Chain	Standard for Pull Models
Approximate Weight	1922 lbs (Lift), 2177 lbs (Pull), 1929 lbs (Semi-Mount)
Options	Single Row Chain Deflectors for Front and Rear
Warranty	1 year limited warranty with a 5 year gearbox limited warranty

FEATURES

- Rear Sloped Deck • High blade tip speeds • Deep sidebands • Quick detach gearbox shields