

Bush Hog® TOUGH 2012 Series Rotary Cutters

BUSH HOG® TOUGH FEATURES
TOUGH 10 Gauge Deck Construction
TOUGH 5 Year Gearbox Limited Warranty
TOUGH 7 Gauge Sidebands
TOUGH Replaceable Wide Skids
TOUGH Cushioned Axle Arms
TOUGH Powder Coat Paint



MODEL	2012
Cutting Width	11 ft 9 inches
Dimensions (width x length)	12 ft 2 inches x 10 ft (Lift), 12 ft 2 inches x 13 ft 4 inches (Pull)
Type Hitch	3 Point Cat. II & III Standard & Quick Hitch, Center Pull Self Leveling or Semi-Mount, Cat. II & III
Cutting Capacity	2 inches
Cutting Height	2 to 12 inches
Deck Thickness	10 gauge
Side Bands	7 gauge /10 inches deep
Minimum Tractor HP	60 PTO (Pull), 70 PTO (Lift)
Driveline	ASAE Category 4
Cross Shaft	Rubber Element
Gearbox HP	120 Main and 90 Outboard
Tractor PTO Speed	540/1000 RPM
Driveline Protection	4 Plate PTO Slip Clutch
Height Adjustment	Choice of Manual Height Bundle or Hydraulic Cylinder
Blade Holder(s)	Round Pans
Blades	1/2 x 4 inches - Corner Uplift
Blade Tip Speed	15,490 FPM/540 RPM; 15,422 FPM/1000 RPM
Tires	Laminated Tire on Lift and Semi-Mount Models, Laminated Tire or 15 inch Automotive Wheel on Pull Models, Used Aircraft Tire on Pull Type Only
Axles	Adjustable Axle Arms for Row Spacing, Choice of Single or Dual Axles on Pull Models
Deflectors	Front Belting and Rear Bands (Chains Optional)
Safety Tow Chain	Standard for Pull Models
Approximate Weight	2184 lbs (Lift), 2267 lbs (Pull), 2079 lbs (Semi-Mount)
Options	Single Row Chain Deflector Front and Rear
Warranty	1 year limited warranty with a 5 year gearbox limited warranty

FEATURES

- Sloped Deck • High blade tip speeds • Deep sidebands • Quick detach gearbox shields

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



P. O. BOX 849
 MOBILE, ALABAMA 36601 USA
 EMAIL: mobile@opico.com
 TEL +1 251 438 9881