

# Bush Hog® TOUGH 406 Series Rotary Cutters

## BUSH HOG® TOUGH FEATURES

**TOUGH** Fabricated 1/4 Inch Thick Deck

**TOUGH** 1/4 Inch Sidebands

**TOUGH** 3 Inch x 1 1/2 Inch x 1/4 Inch Channel Strongbacks

**TOUGH** Heavy Duty A Frame and Tail Wheel Bracket

**TOUGH** Extra Heavy Duty Blade Pan

**TOUGH** Extra Heavy Duty Bush Hog Blades

**TOUGH** Powder Coat Paint



**406**

MODEL	
Cutting Width	6 ft
Cutting Capacity	Up to 4 inch Diameter
Cutting Height	2 to 12 inches
Dimensions (width x length)	93 1/2 x 138 inches (Pull Model with Wheels Outside)
Type Hitch	3 Point Lift Cat. II, III & Quick Hitch or Pull with standard safety tow chain
Deck Thickness	1/4 inch
Sidebands	1/4 x 8 inches
Driveshaft	ASAE Category 5
Gearbox	540 RPM, Extra Heavy Duty 125 HP
Tractor PTO Speed	540 RPM
Driveline Protection	Regular duty slip clutch standard or heavy duty slip clutch available
Blade Holder(s)	Round
Blades	5/8 x 5 inches, Extra heavy duty
Blade Tip Speed	10,179 FPM
Tires	Laminated, Caster Wheel
Minimum Tractor HP	60 PTO (Lift) & 50 PTO (Pull)
Front and Rear Deflectors	Front Chains Standard, Rear Chains Optional
Approximate Weight	1524 lbs (Lift Model with Single Tailwheel)
Warranty	1 year limited warranty with a 1 year gearbox limited warranty
Options	Rear Chains, Category I Hitch Pin Bundle

## FEATURES

- Floating top link



P. O. BOX 849  
MOBILE, ALABAMA 36601 USA  
EMAIL: [mobile@opico.com](mailto:mobile@opico.com)  
TEL +1 251 438 9881