

Bush Hog® TOUGH Side Mount Rotary Cutters

BUSH HOG® TOUGH FEATURES

TOUGH 10 Gauge Deck And Sidebands

TOUGH Anti-Cavitation Protection

TOUGH Cast Iron Pump

TOUGH Round Bladeholder

TOUGH Hydraulic Relief Valves Provide Overload Protection

TOUGH Powder Coat Paint



MODEL	SM60
Cutting Width	5 ft
Cutting Capacity	1 inch
Dimensions (transport width x length)	10 ft 5 inches x 5 ft
Minimum Tractor Weight	6000 lbs
Minimum Tractor Lift Capacity	3200 lbs (at 24 inches behind lift pins)
Type Hitch	Category II Standard, Cat. II & III Quick Hitch
Deck Thickness	10 gauge
Tractor PTO Speed	540/1000 RPM
Blade Holder	Round
Type Blades	1/2 x 3 inches, Double Edge
Blade Tip Speed	17,300 FPM at 540 RPM
Blade RPM	1100
Blade Rotation	Clockwise, but Reversible
Cutter Head Movement	90° Up to 85° Down
Driveline	ASAE Category 4, 540 or 1000 RPM
Hydraulic Pump Mounting	Machine Only, PTO Driven
Hydraulic Oil Capacity	35 Gallons, Factory Filled
Hydraulic Capacity	24 GPM
Overload Protection	Hydraulic Relief Valve
Counterweight	275 lbs Standard
Max. Extension of Cutterhead	145 inches from Tractor Centerline
Extension Arm Travel	31 1/4 inches
Approximate Weight	1675 lbs
Deflectors	Standard Equipment
Options	Side Gauge Wheel with Laminated or Solid Tire, Tailwheel Assembly for Mainframe with Laminated Tire, Valve Stand, Chain Shielding
Warranty	1 year limited warranty



P. O. BOX 849
MOBILE, ALABAMA 36601 USA
EMAIL: mobile@opico.com
TEL +1 251 438 9881