

# Bush Hog® TOUGH SQUEALER® Series Rotary Cutters

## BUSH HOG® TOUGH FEATURES

TOUGH EZ Clean Sloped Decks

TOUGH Sidebands With Welded Skids

TOUGH EZ Lube Drivelines

TOUGH Bush Hog® Gearboxes

TOUGH Quick Detach Gearbox Shields

TOUGH Full Length Replaceable Skids

TOUGH Powder Coat Paint



Model SQ160

MODELS	SQ142	SQ148	SQ160	SQ172	SQ184
<b>Cutting Width</b>	3 ft 6 inches	4 ft	5 ft	6 ft	7 ft
<b>Cutting Capacity</b>	1 inch dia.	1 inch dia.	2 inch dia.	2 inch dia.	2 inch dia.
<b>Cutting Height</b>	2 to 12 inches	2 to 12 inches	2 to 12 inches	2 to 12 inches	2 to 12 inches
<b>Dimensions (width x length)</b>	3 ft 7 inches x 6 ft 7 inches	4 ft 3 inches x 7 ft 1 inch	5 ft 5 inches x 8 ft 1 inch	6 ft 5 inches x 9 ft 2 inches	7 ft 5 inches x 10 ft 6 inches
<b>Type Hitch</b>	Cat I Standard and Quick Hitch	Cat I Standard and Quick Hitch	Cat I Standard and Quick Hitch	Cat I Standard and Quick Hitch	Cat I or II Standard and Quick Hitch
<b>Deck Thickness</b>	11 gauge	11 gauge	11 gauge	10 gauge	10 gauge
<b>Sidebands</b>	9 <sup>3</sup> / <sub>4</sub> inches x 11 gauge	10 inches x 11 gauge	9 <sup>3</sup> / <sub>4</sub> inches x 11 gauge	9 <sup>3</sup> / <sub>4</sub> inches x 10 gauge	10 <sup>1</sup> / <sub>4</sub> inches x 10 gauge
<b>Driveshaft</b>	ASAE Cat 3	ASAE Cat 3	ASAE Cat 3	ASAE Cat 3	ASAE Cat 4
<b>Gearbox</b>	45 HP	45 HP	65 HP	65 HP	90 HP
<b>Tractor PTO Speed</b>	540 RPM	540 RPM	540 RPM	540 RPM	540 RPM
<b>Driveline Protection</b>	1/2 x 3 inches Grade 2 shearbolt	1/2 x 3 inches Grade 2 shearbolt	8 x 45 mm Metric Gr. 8.8 shearbolt Slip Clutch/Optional	10 x 55 mm Metric Gr. 8.8 shearbolt Slip Clutch/Optional	Slip Clutch Standard
<b>Blade Holder(s)</b>	Straight	Oval type	Oval type	Oval type	Oval type
<b>Blades</b>	3/8 x 3 inch uplift	3/8 x 3 inch uplift	1/2 x 4 inch uplift	1/2 x 4 inch uplift	1/2 x 4 inch uplift
<b>Blade Tip Speed</b>	11,400 FPM	13,029 FPM	14,335 FPM	14,963 FPM	14,963 FPM
<b>Tires</b>	Laminated or Solid Rubber	Laminated or Solid Rubber	Laminated or Solid Rubber	Laminated or Solid Rubber	Laminated
<b>Tractor HP Range</b>	10 - 25 PTO	15 - 30 PTO	25 - 40 PTO	30 - 45 PTO	50 - 70 PTO
<b>Front and Rear Deflectors</b>	Standard (Front Belting/Rear Band), All 5 Models				
<b>Approximate Weight</b>	397 lbs	455 lbs	636 lbs	764 lbs	1024 lbs
<b>Warranty</b>	1 year limited warranty with a 5 year gearbox limited warranty				
<b>Options</b>	Oval Blade Pan, Chain Shielding	Chain Shielding	Chain Shielding	Chain Shielding	Chain Shielding

## FEATURES

Floating Frame Hitch • High blade tip speeds • Available in major tractor colors

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



P. O. BOX 849  
MOBILE, ALABAMA 36601 USA  
EMAIL: [mobile@opico.com](mailto:mobile@opico.com)  
TEL +1 251 438 9881