

MOBILITY 600 - PTO UNIT



MOBILITY

MODEL 600 PTO 200 Cubic Ft. Capacity

- Dependable field performance – season after season.
- Built tough to be tough, offers maximum payload and minimum maintenance, which adds up to lower cost of operation.
- High clearance PTO shaft. Virtually eliminates PTO damage.
- Longer tongue means smoother trailer-ing.
- Box material and gussets are all stainless steel above the frame.
- Walking beam tandem suspension cuts bump impact 50%. Helps keep spreader stable – Boost accuracy.
- Proven history and performance for over 30 years.
- Another high-class spreader in the Mobility line to fit any budget.

SERVICE PARTS FOR TOTE, MOBILITY, JTI EQUIPMENT & MODEL 10 VITON PUMP





- Stainless steel apron chain and drive chain.
- Stainless steel side hill flo divider.



- Hydraulic On/Off for conveyor.



- 2-Speed drive with stainless steel chain.
- Drive tire and wheel attached to axle-tube for positive contact – no matter how far axle walks.



- Dual gearbox driven spinners with adjustable bolt on fins.
- Spreads 50 Ft. with dual spinners.
- Wrap around rear bumper.

SPECIFICATIONS:

- **OVERALL HEIGHT = 92" w/16.5 L x 16.1 TIRES**
- **OVERALL LENGTH = 205"**
- **OVERALL WIDTH = 96"**
- **WHEEL TRACK = 76"**
- **EMPTY WEIGHT = 3100#**

OPTIONAL:

- **HYDRAULIC ON/OFF FOR CONVEYOR**
- **ROLL-OVER TARP**
- **2 & 4 WHEEL HYDRAULIC SURGE BRAKES**
- **FENDERS**

STANDARD EQUIPMENT INCLUDES:

Walking Beam Tandem Suspension
 8-Bolt Heavy Duty Hubs
 2-Speed Conveyor Drive
 Jack – 5000 LB Swivel
 Safety Chains
 Tarp – Heavy Duty Vinyl
 Tires, 16.5 L x 16.1



P. O. BOX 849
 MOBILE, ALABAMA 36601 USA
 EMAIL: mobile@opico.com
 TEL +1 251 438 9881

7/14/03