

Special Bedshaping Equipment by *Ferguson*



Model 80-80 Ferguson Tilrovator with SW-2-38-7 Bedshaper. P.T.O. driven tiller mulches clods while bedshaper (attached to rear frame bar) shapes beds to uniform dimensions: height of bed from 3" to 9". Above photo demonstrates shaping of wide vegetable bed 7" high and 61" across top. Available for most row spacings. Auxiliary bar may be attached to adapt unit planters for once-over planting operation.

Two-row Bedshaper-Sled adjustable 36"-38" rows; 7" high bed, 12"-14" across top. Uniform shaped beds for transplanting or direct seeding. Extended pontoons and frame enables you to attach transplanters and maintain bed while planting.

SW-4-36-4 Bedshaper. This model used for 4-28"-36" row spacing. Bedshaper shapes bed 4" in height — approximately 24" wide on top. Height of bed determined by size of individual row dividers. Row dividers are available in 2", 4", 5" and 7" heights. Bed heights up to 4" can be attained from flat-worked field. Pre-marked or listed rows required for bed heights exceeding 4" to insure uniform beds. These units may be attached to Ferguson model power-driven tilrovators or to 3-pt. mounted tool bars, either diamond or horizontal.



DISTRIBUTED BY



P. O. BOX 849
MOBILE, ALABAMA 36601 USA
EMAIL: mobile@opico.com
TEL +1 251 438 9881

THE FERGUSON MFG. CO., INC., P.O. BOX 1098, SUFFOLK, VA. 23434