

3500

TWIN-LINE® PLANTER

The only 6 row and 8 row planter offering all the options for the way you farm!



3500 Twin-Line® 6 Row N (30") with Liquid Fertilizer, Squeeze Pump and Double Disc Fertilizer Opener Packages

FROM THE FIELD TO THE ROAD IN SECONDS.

The exclusive Kinze® lift and rotate system allows you to fold and transport in-line as narrow as 11' 2", even with Interplant® packages or fertilizer options. Available in 6 and 8 row configurations, the rigid, non-flex frame of the 3500 Twin-Line planter is perfect for conventional, mulch-till, ridge-till or moderate no-till planting.

KPM III ELECTRONIC SEED MONITOR

- Available with either magnetic or radar distance sensor options.
- Console features a single LCD to display seed count and alphanumeric planting data.
- Segmented bar graphs display up to 36 rows simultaneously in front/rear or left/right configurations.
- Alphanumeric data includes speed, row spacing, seed spacing (by row or overall average) and seed population (by row or overall average).
- Multiple area counters (40) allow total field areas to be compiled.
- Audible alarms and LCD backlighting are all programmable.

FERTILIZER OPTIONS

Increase the efficiency of your operation by utilizing the liquid fertilizer packages on the 3500 Twin-Line planter, available with total capacity of 300 gallons (two 150 gallon tanks). Liquid fertilizer piston pump packages include CDS-John Blue® heavy duty squeeze pumps or CDS-John Blue® piston pumps, flow dividers and ground drive system. Or select a dry fertilizer package with total capacity of 1,650 – 2,200 lbs. depending on your row configuration.

Fertilizer openers are available for use in any tillage system. Choose from heavy duty, notched single disc or double disc fertilizer openers. If more depth control is needed, you can add optional notched single disc opener depth/gauge wheels.

KINZE EDGEVAC®

- The leading edge in vacuum seed metering.
- Excellent seed spacing and population control.
- Consistent seed drop from the edge.
- Less tumbling action or ricochet effect inside seed tube.
- Fewer moving parts, less service and maintenance.
- Self-adjusts to maintain the vacuum seal.



KINZE
WWW.KINZE.COM

3500

TWIN-LINE® PLANTER



SPECIFICATION

Number of Rows	6	8
Row Spacing	30"	30"
Weight Empty (Mechanical)	5,163 lb.	5,854 lb.
Weight Empty (EdgeVac)	5,443 lb.	6,169 lb.
Transport Height	10' 6"	10' 6"
Operation Length	19' 8"	19' 8"
Transport Length	23' 9"	26' 5"
Operation Width	16' 10"	21' 10"
Transport Width	11' 2"	11' 2"

KEY FEATURES

- **Contact Drive System** – spring-loaded contact drive tires eliminate mechanical clutches and smoothes the engagement and disengagement of the drive – helping to reduce residue, rock and mud problems.
- **Precision-Cut, Plated Sprockets and Easy-Access, End-Mounted Transmissions** – easily change rates. An integrated wrench and idler arm tensions the chain. Shear pin protection is built into the lower shaft of the transmission.
- **Throwout Clutch** – shut off the entire Interplant® system drive with just a quarter turn. No need to remove chains or disengage each row unit. It's quick and easily accessible.
- **Telescoping Tongue** – with a height adjustable double-clevis hitch, can be set in three 15" increments to accommodate various single or dual tractor tire arrangements.
- **Low-Profile, Two-Fold Row Markers** – equipped with 16" diameter solid marker blades. Keeps transportation heights under 11 feet.
- **Rugged, Reinforced Double Toolbar** – a clean, uncluttered double toolbar adds strength and weight to the machine where it belongs, for tough planting conditions.
- **Transport Latch Post** – features a spring-loaded safety latch which automatically locks the toolbar in-line when folding for transport. When the planter is unfolding, the latch is released automatically by a small hydraulic cylinder in sequence with the rotation cylinder.

MORE OPTIONS

- Electronic Seed Monitors (KPM III)
- Tractor Mounted PTO Hydraulic Pump (On EdgeVac equipped models only.)
- Rubber V Closing Wheels
- Cast Iron Closing Wheels
- Quick-Adjustable Down Force Springs
- Pneumatic Down Pressure Package (Air Compressor Package is Required)
- Half Rate (2 to 1) Drive Reduction Packages
- Rear Trailer Hitch (for use with Liquid Fertilizer Piston Pump Option only)
- Auxiliary Work Light Packages
- Rock Guard Packages (transport wheel arms)
- 2-Point Hitch Adapter
- Row Unit Extension Bracket Packages (to accommodate Coulter Mounted Residue Wheel Attachments)
- Solid Row Interplant® Packages
- Even Row Push Row Unit Packages
- Interplant® Monitor Packages
- Liquid Fertilizer Packages
 - Two 150 gallon tanks with lids
 - Liquid Fertilizer Openers
 - Liquid Fertilizer Pumps
- Dry Fertilizer Packages
 - Double Disc or Notched Single Disc Fertilizer Opener Packages



P. O. BOX 849
MOBILE, ALABAMA 36601 USA
EMAIL: mobile@opico.com
TEL +1 251 438 9881



Kinze Manufacturing, Inc.
1-800 at Exit 216 • Williamsburg, Iowa • 52361-0806 USA
www.KINZE.com